



Approval	 	
Capability		
Standard	UL	IEC
Rated Voltage	600V	1000V
Rated Current	150A	125A
Wire size	18-1/0AWG	0.2-35mm ²
T/W/End plate		15.2/50/-mm
Height(mm)(NS35:7.5/NS35:15/NS32)		62/69.5/67mm
Rated surge voltage/Contamination Class		8KV/3
Stripping length		16mm
Screw thread/Tightening torque	M6/2.5N.m/22Lb-in	
Internal cylindrical gage	B9	
Insulating Material/Inflammability class	PA/V-0	
Specification	Model	Pieces
(1)Terminal block	PC 35	50
(2)Cover		
(3)Fixed bridge	FBI 2-15 FBI 3-15	10 10
(4)阶梯转接桥	STL 35/5	10
(5)Insertion bridge	EB 10-15	30
(6)Isolator bridge bar,10P		
(7)Bridge bar isolator		
(8)Switching bridge	SBH 2-15	1
(9)Separating plate	TS-K	1000
(10)Partition plate thick 1.5mm	TP-PC 35	10
(11)Test plug socket	DSB 6/5/6	100
(12)Test plug socket insulated	DSBJ 4/15/6	
(13)Zack strip	ZB10	200

HOW TO ORDER :

- **P** - -

Customer Request

Series No.

No. of pole

Color

1	Gray	4	Green	7	Transp-arent
2	Blue	5	Orange	8	Yellow
3	Black	6	Red	9	white

 mm (INCH)	 DEGSON ELECTRONICS CO., LTD.
 THROANGLE PROJECTION	NAME PC 35